

MHRJ SERIES

Cat6/6A Plugs



FEATURES:

- Compatible with standard crimping tools
- Compatible with all FCC specifications
- Pass-through plugs available upon request
- Contacts gold over nickel plated as standard, other platings available upon request



ORDER CODE:

EXAMPLE PART NUMBER: MHRJC6R1316

MHRJ	C6	R	1	3	1	6																																													
SERIES	CABLE TYPE		CABLE JACKET OD		CABLE CODE	BOOT OPTION																																													
RJ - PLUG	R - ROUND		<table border="1"> <thead> <tr> <th>#</th> <th>TYPE</th> <th>CABLE OD (accepted by Conn)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td rowspan="2">Conn plug only</td> <td>4.5 – 6.3mm</td> </tr> <tr> <td>2</td> <td>5.9 – 8.5mm</td> </tr> <tr> <th>#</th> <th>TYPE</th> <th>CABLE OD (accepted by boot)</th> </tr> <tr> <td>3</td> <td rowspan="6">Conn plug + boot kit</td> <td>Up to 6.0mm</td> </tr> <tr> <td>4</td> <td>Up to 6.5mm</td> </tr> <tr> <td>5</td> <td>Up to 7.0mm</td> </tr> <tr> <td>6</td> <td>Up to 7.5mm</td> </tr> <tr> <td>7</td> <td>Up to 8.0mm</td> </tr> <tr> <td>8</td> <td>Up to 8.5mm</td> </tr> </tbody> </table>		#	TYPE	CABLE OD (accepted by Conn)	1	Conn plug only	4.5 – 6.3mm	2	5.9 – 8.5mm	#	TYPE	CABLE OD (accepted by boot)	3	Conn plug + boot kit	Up to 6.0mm	4	Up to 6.5mm	5	Up to 7.0mm	6	Up to 7.5mm	7	Up to 8.0mm	8	Up to 8.5mm	<table border="1"> <thead> <tr> <th>#</th> <th>COLOUR</th> </tr> </thead> <tbody> <tr> <td>N</td> <td>NO BOOT</td> </tr> <tr> <td>1</td> <td>BLACK</td> </tr> <tr> <td>2</td> <td>BLUE</td> </tr> <tr> <td>3</td> <td>DK GREY</td> </tr> <tr> <td>4</td> <td>GREEN</td> </tr> <tr> <td>5</td> <td>LT GREY</td> </tr> <tr> <td>6</td> <td>PURPLE</td> </tr> <tr> <td>7</td> <td>RED</td> </tr> <tr> <td>8</td> <td>YELLOW</td> </tr> <tr> <td>9</td> <td>WHITE</td> </tr> </tbody> </table>	#	COLOUR	N	NO BOOT	1	BLACK	2	BLUE	3	DK GREY	4	GREEN	5	LT GREY	6	PURPLE	7	RED	8	YELLOW	9	WHITE
#	TYPE	CABLE OD (accepted by Conn)																																																	
1	Conn plug only	4.5 – 6.3mm																																																	
2		5.9 – 8.5mm																																																	
#	TYPE	CABLE OD (accepted by boot)																																																	
3	Conn plug + boot kit	Up to 6.0mm																																																	
4		Up to 6.5mm																																																	
5		Up to 7.0mm																																																	
6		Up to 7.5mm																																																	
7		Up to 8.0mm																																																	
8		Up to 8.5mm																																																	
#	COLOUR																																																		
N	NO BOOT																																																		
1	BLACK																																																		
2	BLUE																																																		
3	DK GREY																																																		
4	GREEN																																																		
5	LT GREY																																																		
6	PURPLE																																																		
7	RED																																																		
8	YELLOW																																																		
9	WHITE																																																		
PERFORMANCE CATEGORY		WIRE INSULATION OD		<table border="1"> <tbody> <tr> <td>N</td> <td>NO CABLE CLAMP, UNSHIELDED</td> </tr> <tr> <td>1</td> <td>NO CABLE CLAMP, SHIELDED</td> </tr> <tr> <td>2</td> <td>CABLE CLAMP, SHIELDED</td> </tr> </tbody> </table>		N	NO CABLE CLAMP, UNSHIELDED	1	NO CABLE CLAMP, SHIELDED	2	CABLE CLAMP, SHIELDED																																								
N	NO CABLE CLAMP, UNSHIELDED																																																		
1	NO CABLE CLAMP, SHIELDED																																																		
2	CABLE CLAMP, SHIELDED																																																		
<table border="1"> <tbody> <tr> <td>C6</td> <td>CAT6</td> </tr> <tr> <td>C6A</td> <td>CAT6A</td> </tr> </tbody> </table>	C6	CAT6	C6A	CAT6A	<table border="1"> <tbody> <tr> <td>1</td> <td>0.90 – 1.00mm INSULATOR OD (Cat6 only)</td> </tr> <tr> <td>2</td> <td>1.00 – 1.10mm INSULATOR OD (Cat6A only)</td> </tr> <tr> <td>3</td> <td>1.10-1.25mm INSULATOR OD (Cat6A only)</td> </tr> </tbody> </table>		1	0.90 – 1.00mm INSULATOR OD (Cat6 only)	2	1.00 – 1.10mm INSULATOR OD (Cat6A only)	3	1.10-1.25mm INSULATOR OD (Cat6A only)																																							
C6	CAT6																																																		
C6A	CAT6A																																																		
1	0.90 – 1.00mm INSULATOR OD (Cat6 only)																																																		
2	1.00 – 1.10mm INSULATOR OD (Cat6A only)																																																		
3	1.10-1.25mm INSULATOR OD (Cat6A only)																																																		

TECHNICAL SPECIFICATION:

INSULATOR MATERIAL	UL-RATED POLYCARBONATE
CONTACT MATERIAL	COPPER ALLOY
CONTACT PLATING	GOLD (50u") OVER NICKEL PLATED
BOOT MATERIAL	PVC (IF APPLICABLE)
SHIELDING MATERIAL	NICKEL PLATED BRASS (IF APPLICABLE)
MATING CYCLES	2,000 CYCLE MIN.

Simple. Complex. Critical.

Established technologies you can trust.